

**NEA ÜRÜNLERİNİN TEKNİK ÖZELLİKLERİ**

ÜRÜN TİPİ	EĞİLME MUKAVEMETİ	BASINÇ MUKAVEMETİ	BETONA ADERANS (SS 92 35 07)	SERBEST RÖTRE	NEA HALKA TESTİ (SS 92 35 19)
FLOOROPAL M TOP	>8 N / mm <sup>2</sup>	>40 N / mm <sup>2</sup>	>3 N / mm <sup>2</sup>	%0,04-0,06	155-165 mm
FLOOROPAL M FLEX	>10 N/mm <sup>2</sup>	>40 N / mm <sup>2</sup>	>3 N / mm <sup>2</sup>	%0,04-0,06	155-165 mm
FLOOROPAL M X	>10 N/mm <sup>2</sup>	>40 N / mm <sup>2</sup>	>3 N / mm <sup>2</sup>	%0,04-0,06	155-165 mm
FLOOROPAL M 15 ve LC	>7 N / mm <sup>2</sup>	>30 N / mm <sup>2</sup>	>2 N / mm <sup>2</sup>	%0,04-0,06	155-165 mm
FLOOROPAL M 10 ve RAPID	>5 N / mm <sup>2</sup>	>25 N / mm <sup>2</sup>	>1,5 N / mm <sup>2</sup>	%0,04-0,06	155-165 mm
FLOOROPAL M 19 ve RAPID	>4 N / mm <sup>2</sup>	>19 N / mm <sup>2</sup>	>1,5 N / mm <sup>2</sup>	%0,04-0,06	155-165 mm
FLOOROPAL M BASE	>6 N/mm <sup>2</sup>	>25 N / mm <sup>2</sup>	>1,5 N / mm <sup>2</sup>	%0,03-0,05	135-145 mm
FLOOROPAL REPAIR MORTAR	>6 N/mm <sup>2</sup>	>25 N / mm <sup>2</sup>	>1,5 N / mm <sup>2</sup>	%0,03-0,05	135-145 mm
FLOOROPAL MARINE LIGHT	>4 N / mm <sup>2</sup>	>15 N / mm <sup>2</sup>	>1,5 N / mm <sup>2</sup>	%0,03-0,05	135-145 mm
FLOOROPAL MARINE FLEX	>11 N / mm <sup>2</sup>	>30 N / mm <sup>2</sup>	>3 N / mm <sup>2</sup>	%0,04-0,06	155-165 mm